



Computer Memory Test Labs

Intel® Approved Final Test Report

MOTHERBOARD	MANUFACTURER	CHIPSET	TEST #	STATUS
NUC7i7BNH	Intel	Intel® Kaby Lake	027188	PASSED

MEMORY MODULE INFORMATION

CMTL Part #: KIN389

Manufacturer Name: **Kingston**

Manufacturer Part #: **KVR21S15D8/16**

DRAM Manufacturer: **Skhynix**

Environment Code: **RoHS**

DRAM Part #: **H5AN8G8NAFR-UHC Rev A**

Low Profile: **30mm LP**

Module Config: **2048M x 64**

Cas Latency: **15**

Module Size: **16GB**

Bank: **2**

PCB Part #: **2025630-0C1.A00G Rev A**

PCB Layer Count: **10 Layer** Assembly Type: **Single Board/Non Stacked**

Module Information: **Unbuffered 1.2V Non-ECC 2133MHz DDR4 SODIMM**

SYSTEM INFORMATION	TESTING DETAILS
<p><u>MINIMUM SYSTEM INFORMATION</u></p> <p>Minimum System: NUC7i7BNH Serial Number: GEBN711005H8 Board Revision: J31145-302 Bios Memory Count: 16GB Processor Code: Intel® Core™ i7-7567U @ 3.50GHz Bios at time of test: BNKBL357.86A.0042.2017.0303.1854 RST PRO Count: 17G 1008M</p> <p><u>MAXIMUM SYSTEM INFORMATION</u></p> <p>Maximum System: NUC7i7BNH Serial Number: GEBN711005TP Board Revision: J31145-302 Bios Memory Count: 32GB Processor Code: Intel® Core™ i7-7567U @ 3.50GHz Bios at time of test: BNKBL357.86A.0042.2017.0303.1854 R.S.T PRO Count: 33G 1008M</p>	<p>35°C~55°C Temperature / Standard Voltage</p> <p>Start Date: 6/16/2017 Stop Date: 6/17/2017 Insertion Test: Pass SPD Check: Pass Minimum Load: Pass Maximum Load: Pass S0 ~ S5 Test: Pass Power Cycle Test: Pass Test Card Version: R.S.T Premium v8.50</p>

Microsoft Windows-7 64bit version is used as it support over 4GB memory and must support target chipset/CPU platform. All board drivers must be loaded when drivers are available on Intel web site. Front panel power cycling test, ACPI S3 sleep state cycling test, and Hibernate S4/S5 state cycling test is done up to 20 cycle each when the board support it. At least 2 loops of all test under R.S.T PRO3 to be completed.

Test Notes:

Min configuration, 5 Loops Passed, 0 Error; Memory speed running @ 2133MHz
 Max configuration, 5 Loops Passed, 0 Error; Memory speed running @ 2133MHz
 UUT under test reached +35°C



Computer Memory Test Labs

Intel® Approved Final Test Report

MOTHERBOARD	MANUFACTURER	CHIPSET	TEST #	STATUS
NUC7i7BNH	Intel	Intel® Kaby Lake	027188	PASSED

MEMORY MODULE INFORMATION

CMTL Part #: KIN389

Manufacturer Name: **Kingston**

Manufacturer Part #: **KVR21S15D8/16**

DRAM Manufacturer: **Skhynix**

Environment Code: **RoHS**

DRAM Part #: **H5AN8G8NAFR-UHC Rev A**

Low Profile: **30mm LP**

Module Config: **2048M x 64**

Cas Latency: **15**

Module Size: **16GB**

Bank: **2**

PCB Part #: **2025630-0C1.A00G Rev A**

PCB Layer Count: **10 Layer** Assembly Type: **Single Board/Non Stacked**

Module Information: **Unbuffered 1.2V Non-ECC 2133MHz DDR4 SODIMM**

SYSTEM INFORMATION	TESTING DETAILS
<p><u>MINIMUM SYSTEM INFORMATION</u></p> <p>Minimum System: NUC7i7BNH Serial Number: GEBN711005H8 Board Revision: J31145-302 Bios Memory Count: 16GB Processor Code: Intel® Core™ i7-7567U @ 3.50GHz Bios at time of test: BNKBL357.86A.0042.2017.0303.1854 RST PRO Count: 17G 1008M</p> <p><u>MAXIMUM SYSTEM INFORMATION</u></p> <p>Maximum System: NUC7i7BNH Serial Number: GEBN711005TP Board Revision: J31145-302 Bios Memory Count: 32GB Processor Code: Intel® Core™ i7-7567U @ 3.50GHz Bios at time of test: BNKBL357.86A.0042.2017.0303.1854 R.S.T PRO Count: 33G 1008M</p>	<p>35°C~55°C Temperature / Standard Voltage</p> <p>Start Date: 6/16/2017 Stop Date: 6/17/2017 Insertion Test: Pass SPD Check: Pass Minimum Load: Pass Maximum Load: Pass S0 ~ S5 Test: Pass Power Cycle Test: Pass Test Card Version: R.S.T Premium v8.50</p>

Microsoft Windows-7 64bit version is used as it support over 4GB memory and must support target chipset/CPU platform. All board drivers must be loaded when drivers are available on Intel web site. Front panel power cycling test, ACPI S3 sleep state cycling test, and Hibernate S4/S5 state cycling test is done up to 20 cycle each when the board support it. At least 2 loops of all test under R.S.T PRO3 to be completed.

Test Notes:

Min configuration, 5 Loops Passed, 0 Error; Memory speed running @ 2133MHz
 Max configuration, 5 Loops Passed, 0 Error; Memory speed running @ 2133MHz
 UUT under test reached +35°C